

ECOTEL[®] 3G

UMTS gateway with configurable VoIP – PSTN options



- Converts fixed-to-mobile calls into cost-saving mobile-to-mobile calls
- Mobile Internet broad band access through HSDPA
- Landline replacement
- Backup for voice and internet through mobile connection
- Integrated SIP Server
- Toll-grade voice compression, T.38 fax support
- Email to SMS conversion
- Autoprovisioning available

Reduce your telephony costs

Connect your current PBX to the world of Mobile and VoIP. With low per-port implementation costs, the ECOTEL 3G supports up to 4 mobile channels, 8 VoIP channels, and different telephony options.

Eliminate the expense of international calls placed from mobile phones. The ECOTEL 3G delivers Call Through and Call Back dialing and thereby maximizes your existing VoIP infrastructure.

Save time and effort during installation as a result of built-in, designed compatibility. .

Simple installation and sophisticated management

In minutes, install the ECOTEL 3G and make your first phone calls. Just connect the cables and the power and physical installation is complete. Then, use the ECOTEL 3G's Quickstart tool to complete initial configuration.

To fine-tune the routing configuration, use our GATE Manager. Finally, you can use the TELES NMS (Network Management System) for remote provisioning of bulk installations; the ECOTEL 3G can automatically receive updated routing files from the NMS.

Savings with Least Cost Routing

Save money on every phone call. The ECOTEL 3G delivers phone-number prefix recognition. This enables the gateway to direct calls to a specific channel that contains a SIM card from the corresponding UMTS network.

Remote survivability

Protect your ability to make phone calls. If your office is disconnected from its VoIP network server, ECOTEL 3G can route both interoffice calls and PSTN calls. IP phones continue to function thereby sustaining your productivity.

Backup your internet connection with the ECOTEL 3G via mobile network connectivity.

Mobil data connectivity

The ECOTEL 3G can also replace your landline and make you and your office mobile. Access the internet wherever you want with a broadband connection of up to 14.4 Mbps through HSDPA.

Use your VoIPBox as a Hot Spot entry point with a WIFI USB Stick.

CAPABILITIES

Scalability	4 UMTS/HSDPA channels 1 SIM per channel or vGATE SIM server (optional) 1 Extension Module (FXS, FXO, BRI, LCR) 8 VoIP channels
VoIP codecs	G.711, G.723, G.726, G.728, G.729, GSM
Fax support	T.38, fallback to G.711
Echo cancellation	G.168 – 2002, 128 ms tail length
DTMF	RFC 2833, SIP/H.323 info, inband
VoIP quality	Configurable ToS, Diffserv, VLAN Silence suppression, VAD, CNG, G.729B QoS alternative routing based on ASR, fraction lost, jitter, and roundtrip delay. Traffic shaping Dynamic PSTN fallback (IntraStar patent)
Call routing	Time-dependent routing Multilevel alternative routing 5000 routing entries ENUM support Database managed routing Support for multiple gatekeepers, H.225 (v4) Support for multiple registrars Overlap/en-bloc conversion RFC 3578 Digit manipulation Black/white list
Data access	Integrated IP router via GPRS/EDGE/UMTS/HSDPA Up to 14.4 Mbps in downlink Up to 768 kbps in uplink Integrated DSL router (PPPoE) DHCP server and client Firewall support VPN support
Advanced	Integrated SIP registrar and location server (Metering tone (12/16 kHz) → only FXS) Integrated callback/two-stage-dialing server CLIP RTP multiplex bandwidth reduction STUN support Symmetric RTP (COMEDIA) Radius support
UMTS specific	Full vGATE SIM Server support (optional) Alert/busy tone detection Announcement recognition E-mail to SMS conversion QoS routing: automatic blocking of GSM/UMTS ports based on ASR, announcements or network errors

PROTOCOLS

Mobile	UMTS 850/1900/2100 MHz GSM quadband 850/900/1800/1900 MHz Prepared for UMTS AWS (1700) (on demand)
VoIP	SIP (RFC 3261), H.323 (v4)
ISDN	DSS1 (Q.931, national variants), Q.SIG-BC TE/NT, PP/PMP (BRI only)

SYSTEM MANAGEMENT

Remote access via IP with NMS or GATE Manager
HTML configuration interface
SNMP (alarm management)
Call Detail Records (CDRs)

CONNECTION SPECIFICATIONS

Ethernet	2 × Ethernet 10/100 Base-T RJ-45
USB	USB 2.0
Analog	4 ports RJ-11 (optional)
ISDN	2 ports RJ-45 (optional)
Antenna	SMA (1 antenna for 4 channels)

PHYSICAL PARAMETERS

Size (W × H × D)	280 mm × 38 mm × 138 mm
Material	ABS, black
Mounting	Desktop, wall
Power supply	Wall power supply, 12 VDC, 1.6 A

CERTIFICATES

EMC, Safety, CE, FCC

ADDITIONAL FEATURES

Mass Storage support	} supported with later roadmap
USB Stick configuration support	
Generic Printer Support via TCP/IP (USB)	
WIFI Support via USB (Server and Client)	

VoIPBox	UMTS ports	VoIP ports	FXS ports	FXO ports	BRI ports
3G	4	8	–	–	–
3G FXS	4	8	4	–	–
3G FXx	4	8	2	2	–
3G BRI	4	8	–	–	2
3G FXO on demand	4	8	–	4	–

Find out more: www.teles.com



TELES
AG
Informationstechnologien

TELES AG | HEADQUARTERS

Ernst-Reuter-Platz 8

10587 Berlin

GERMANY

Phone +49 30 399 28 - 066

Fax +49 30 399 28 - 051

E-mail sales@teles.com